



MiniMax FS30 smart

410 mm combined surface-thicknesser 300 mm version



The FS 30 is a rigid and robust machine with a steel base and cast iron thicknesser worktables able to machine components of large dimensions guaranteeing maximum machining precision and the complete absence of vibration.

The FS 30 Smart combined surfacer - thicknesser with worktable widths from 300 mm has been completely renewed.

New version features technical solutions making it easier and more practical to use:

- Control panel easily accessible from all operator positions.
- Planing fence secured to the infeed table to ensure better support during machining.
- Improved feed roller system for heavy stock removal.
- New planing table opening system enables the machine to be placed against walls thus saving workshop space.
- Larger planing tables and one-piece steel base ensure maximum stability and a top class finish.

Technical specifications

Planer unit

total length of the tables	1510mm
working width	300mm
spindle speed	5200g/min
number of knives	3
max depth of cut	4mm
tilting fence	0 - 45 °

Thicknesser unit

table dimensions	565x300mm
max/min thicknessing capacity	3/230mm
max stock removal	4mm
feed speed	7m/min
hp - kw - hz	4 - 3 - 50
overall dimensions without packaging	1700x1400mm
net weight	285kg

Further optionals

Mortiser

wescott spindle	
cutter block with "Tersa" disposable knives	
available with single-phase motor	2,5hp 50Hz (4,8Hp 60Hz)

available with three-phase motor

5,5hp 50Hz
(6,6Hp 60Hz)